

Cu29, Inaugural Model

Calibre

Reference No.	AC 003 ALCHEMISTS CALIBRE 003
Movement	Manual-winding mechanical manufacture movement, engraved and hand-bevelled double barrel linked in parallel, suspended "moustache" dual pawl winding. Ébauches in Cuprum 479, titanium and stainless steel. Entire calibre hand-finished, traditionally buffed and polished corners, rounded and hand-polished balance bridge and sweep second cock, escapement wheel, black-polished endstones, rounded and moveable Geneva hairspring stud holder. Moulded, ringed and bevelled wheel and intermediate wheels, black-polished and hand-blued screws, numbered calibre.
Diameter	38 mm or 17 lignes
Functions	Hours and minutes offset at 12 o'clock, subsidiary seconds at 6 o'clock, power reserve displayed via peripheral gear bar, function selector.
Power reserve	72 chronometric hours
Frequency	21,600 vib/hour, 3 Hz
Balance	Variable inertia balance with weight screw
Balance spring	Cylindrical, blued
Escapement	Swiss lever, 15 teeth
Rubies	56
Number of components	362

Case

Case	Round with specific "atmosphere"-shaped sapphire crystal
Material	Cuprum 479
Diameter	44 mm
Total thickness	15.40 mm, top of crystal
Crown	Cuprum 479
Case back	Engraved Cuprum 479
Lugs	20 mm



Buckle

Dials-Hands

Dial hours minutes and subsidiary seconds	Cuprum 479 base with rounded natural gemstones, Aventurines or traditional <i>Grand Feu</i> enamel
Power reserve and selector dial	Circular grained stainless steel, lacquered engraving
Hands hours minutes and seconds	Rounded, blued or lacquered or Cuprum 479
Power reserve indicator	Blued steel shape
Selector hand	Blued flat sword hands
	Strap
Strap	Alligator leather, matt black

Other Information

In Cuprum 479, pin buckle (ardillon)

Water resistance 30 metres	
----------------------------	--